

# IND-SPHINX<sup>®</sup>

PCB DRILLS | PCB ROUTERS  
PCB SPECIALS

DEPANELING  
ROUTING BITS

Proudly  
Made in India  
Since 1989

IND-SPHINX Ø 0.050 mm

AXIS EUROPE GmbH

Danziger Str. 3, 88250 Weingarten, Germany  
49 (0)751 560 1589 - 0 info@axis-europe.eu  
www.axis-europe.eu



IND - SPHINX PRECISION LTD

Plot Number 28, Sector 5, Parwanoo  
Himachal Pradesh India 173220  
+91 1792 232860 / 232960  
customerfocus@indsphinx.com www.indsphinx.com

www.indsphinx.com


QUALITY • PRECISION • CONSISTENCY



## HIGH PERFORMANCE DEPANELING ROUTER

P650

d	l
1.40*	7.00
1.50*	8.00
1.60	8.00
1.80*	8.00
2.00	8.00
2.40*	10.50
2.50	10.50




Compatible for machine with Upward Vacuum

## CHIP BREAKER ROUTER

P726

d	l
0.40*	2.00 - -
0.50* / 0.60*	3.00 4.00 -
0.70*	4.00 5.00 -
0.80	5.00 6.00 7.00*
0.90	5.00 6.00 7.00*
1.00	5.00 7.00 8.50*
1.10*	5.00 7.00 8.50*
1.20	5.00 7.00 8.50*
1.30* - 1.40*	5.00 7.00 8.50*
1.50	8.50 - -
1.60	8.50 - -
1.70* - 1.90*	8.50 - -
2.00	9.00 - -
2.10*	9.00 - -
2.40*	9.00 - -
2.50* - 2.90*	9.00 - -
3.00* / 3.175*	9.00 - -




Compatible for machine with Upward Vacuum

## DIAMOND CUT ROUTER

P627

d	l
0.70*	5.00 -
0.80* / 0.90*	5.00 7.00
1.00	5.00 7.00
1.10*	5.00 7.00
1.20	5.00 7.00
1.30*	5.00 7.00
1.40*	5.00 7.00
1.50 / 1.60	8.50 -
1.80	8.50 -
2.00	9.00 10.50
2.10* / 2.20*	9.00 10.50*
2.30	9.00 10.50*
2.40	9.00 10.50
2.50	9.00 10.50
2.60* / 2.80*	9.00 -
2.90*	9.00 -
3.00* / 3.175*	9.00 10.50




Compatible for machine with Downward Vacuum

## CHIP BREAKER ROUTER

P727

d	l
0.40*	2.00 - -
0.50* / 0.60*	3.00 4.00 -
0.70*	4.00 5.00 -
0.80	5.00 6.00 7.00*
0.90	5.00 6.00 7.00*
1.00	5.00 7.00 8.50*
1.10*	5.00 7.00 8.50*
1.20	5.00 7.00 8.50*
1.30* - 1.40*	5.00 7.00 8.50*
1.50	8.50 - -
1.60	8.50 - -
1.70* - 1.90*	8.50 - -
2.00	9.00 - -
2.10*	9.00 - -
2.40*	9.00 - -
2.50* - 2.90*	9.00 - -
3.00* / 3.175*	9.00 - -



Compatible for machine with Downward Vacuum

All dimensions are in mm

D : Ø 1/8" (3.175 mm) Common Shank

On Request Shank Dia 3mm